### **VSL HEAVY LIFTING**





HANDLING OF EXCEPTIONAL LOADS

SPECIAL EQUIPMENT

CUSTOMISED SOLUTIONS

# **VSL - YOUR PARTNER FOR DESIGN, CONSTRU**

#### **VSL INTERNATIONAL**

The VSL organisation has grown from being a small Swiss post-tensioning subcontractor to an acknowledged world leader in special construction methods since its first commercial application of the VSL Post-Tensioning system in 1956.

#### **WORLDWIDE NETWORK**

VSL operates through 60 locations as a worldwide network, which includes technical centres located in Switzerland and Singapore as well as production facilities in Spain, Thailand and China. The group's 4,600 employees – including 900 engineers and technicians – provide a full range of construction services, from project planning and consultancy through to the execution of the work on site including construction engineering and technical support.

#### VSL – A COMMITMENT TO QUALITY, SAFETY AND SUSTAINABLE DEVELOPMENT

VSL has put in place rigorous policies for quality, safety and sustainable development in keeping with its position as a leading specialist contractor. Proactive management systems have been established to address local needs while ensuring uniform high standards throughout the company's network.

VSL recognises that its employees are the key to competitiveness, efficiency and safe working practices. The company is committed to "Safety first" and strives for "Zero Accident" operations by motivating and empowering its employees to act responsibly in order to achieve these goals.

#### SUSTAINABLE DEVELOPMENT

For VSL, sustainable development means striking a balance in its activities between the economic profitability of its business operations and their social and environmental impacts.



#### **VSL HEAVY LIFTING**

VSL Heavy Lifting has carried out hundreds of challenging projects all over the world – involving an incredible variety of different applications – and has set many new records in the process.

Its unrivalled specialist experience has been gained on projects where it has lifted, lowered, slid and tilted loads for everything from bridges to skyscrapers, offshore platforms to sports stadiums. The business started successfully in 1970 with the lifting of two silo roofs at Portoscuso in Sardinia, Italy. A further milestone soon followed in 1971 with the lifting and tensioning of the roof structure of Munich's world-famous Olympic Stadium.

The VSL strand lifting system is at the heart of all heavy lift operations and, in an ever-more eco-conscious world, contributes to delivering sustainable solutions as it has only minimal environmental impact. A strand lifting unit has the capacity to move 300 to 500 times its own weight – in comparison the ratio for a crane might be as low as one, depending on the situation. As a result, the resources required to mobilise the VSL equipment on site are substantially lower, which makes heavy lifting a far more environmentally friendly solution.



CREATIN

G

VSL designed and built a 1.3km-long six-lane cable-stayed bridge, connecting the western coastline of Abu Dhabi with Hodariyat Island. Hodariyat Bridge, Abu Dhabi - UAE (2009-2012)

# **CTION AND RELATED SERVICES WORLDWIDE**



WWW.VSL-HEAVY-LIFTING.COM WWW.VSL.COM

# **HEAVY LOADS – POSITIONED WITH SKILL**

**CUSTOM-ENGINEERED SOLUTIONS FOR MOVING LARGE STRUCTURES** 



#### TAILORED SERVICES

VSL offers a complete range of services from initial concept through to the engineering, planning, equipment supply and execution of any kind of heavy lifting project.

The approach is flexible and the scope of the services provided by VSL is tailored to specific project requirements. VSL operates worldwide, delivering the most appropriate solutions for each project.

- / Feasibility studies and preliminary consultation for lifting, lowering, sliding, skidding, tilting and jacking operations
- / Project design and planning, equipment specification, scheduling and budgeting
- / Design, manufacture and supply of specialist equipment and temporary structures
- / Rental and operation of VSL equipment
- / Execution of the heavy lifting operation

### JACKING





## C R E A T I N G S O L U







### **BENEFITS TO CLIENTS**

#### ECONOMY

- / Cost-effective and practical methods for carrying out complex operations
- / Considerable time-savings
- / Decreased usage of cranes
- / Reduced need for temporary supports and falsework

#### SAFETY

- / Increased safety through the use of customised methods
- / Controlled and well-managed working procedures
- / Reduced need for working at heights thanks to ground-level assembly of large structural elements
- / Controlled handling of loads
- / Fail-safe methods using a strand jacking system that keeps the load mechanically secured even in the unlikely event of an electrical or hydraulic fault

#### QUALITY

- / Collaboration at every step from early design onwards
- / Soundly engineered systems and methods
- / Reliable operations drawing on long experience
- / Non-invasive operations with minimum impact on the load being handled

#### ENVIRONMENT

- / Minimum environmental impact
- / Use of biodegradable fluids
- / Low energy consumption

#### RELIABLE SUPPORT

- / Nearly 50 years of experience in heavy lifting works, including design and execution together with equipment provision and operation
- / Operations backed by a worldwide network and the complete range of VSL products and services

### ALL OPERATIONS CARRIED OUT TO RECOGNISED INTERNATIONAL STANDARDS

ISO 9001: 2008 Quality Management System

ISO 14001: 2004 Environmental Management

**OHSAS 18001: 2007** Occupational health and safety management systems.

# THE VSL'S HEAVY LIFTING SYSTEMS

### THE VSL STRAND JACKING SYSTEM

VSL's hydraulic strand jacking system is designed for the lifting, lowering, sliding and tilting of loads.

The system's main components are a motive unit, a tension member (made up of strands and an anchorage for the load), a hydraulic pump and a monitoring and control system.

#### **MOTIVE UNIT**

The motive unit consists of a hydraulic center-hole jack together with upper and lower anchorages.

The upper anchorage is attached to the jack's piston. When the hydraulic jack extends, the strands are gripped by the wedges in the upper anchorage and move upwards.

When the piston starts its downward movement ready for the next stroke, strands are gripped by the wedges in the bottom anchorage. The upper anchorage opens at the same time.

This sequence is repeated to move the load in a step-by-step process. For lowering operations, VSL motive units are equipped with a device that automatically controls the opening and closing of the anchorages.

#### **TENSION MEMBER**

The tension member consists of 7-wire steel prestressing strands of 15.24 mm nominal diameter. It is anchored to the load by a specially designed end anchorage.

#### **HYDRAULIC PUMP**

The oil flow for the motive units is provided by electro-hydraulic pumps with either single or multiple outlets.

The characteristics of these pumps guarantee synchronised jacking, even under variable loads. Built-in pressure gauges or remote pressure control devices allow monitoring at all times.

The size of the pump is chosen to suit the load being moved. The movement speed depends on the project requirements and can exceed 20 m/hour, if required.







To lift the cable-net roof of a major stadium, two strand jacking units were installed at each lifting point on the compression ring. Each pump served up to seven lifting points. Maracanã Stadium, Rio de Janeiro - Brazil (2013)

CREATING





#### **CONTROL AND MONITORING**

The VSL jacking system enables precisioncontrolled movement to within millimetres, whether operated manually or by remote control.

This precise coordination of all movements across every part of the system is achieved by using specially designed, computer-based multi-point monitoring systems.

#### **KEY DATA FOR VSL STRAND LIFTING UNITS**

#### SPECIAL FEATURES

- / The VSL strand jacking system is lightweight and easy to handle
- / The load is secured at every step of the operation
- The efficient, compact modular system is easily adaptable to client and project requirements

ТҮРЕ	CAPACITY <sup>1</sup>	MAX. NUMBERS OF STRANDS	CABLE DIAMETER	BODY DIMENSIONS		WEIGHT <sup>2</sup>
	kN		mm	Height mm	Width/Depth mm	kg
SLU-10 SMU-10	104	1	16	1536	270/270	95
SLU-40 SMU-40	416	4	67	1952	360/360	280
SLU-70 SMU-70	728	7	82	2517	460/460	530
SLU-120 SMU-120	1248	12	117	2657	520/520	750
SLU-220 SMU-220	2288	22	167	3064	520/520	1790
SLU-330 SMU-330	3224	31	191	3074	650/650	2080
SLU-580 SMU-580	5720	55	254	3280	790/790	4500

All technical data are based on VSL standard equipment.

Piston strokes vary between 160 mm and 550 mm, depending on the type of unit.

<sup>1</sup> Capacity is based on Y1860S7.15.2 strands in accordance with the requirements of EN 10138:2009; or grade 1860 [270] -15 strands meeting ASTM A416/416M-10 with a safety factor of s=2,5 with respect to the minimum breaking force of the strands.

<sup>2</sup> Body dimensions and weight listed are for the basic version of the SLU lifting units with the maximum piston stroke.

### THE VSL SKIDDING SYSTEM

The VSL hydraulic skidding system (VSS) is designed for moving heavy loads along the ground in any direction, even over long distances. The system's main components are skid shoes, pushpull units, skid tracks, hydraulic pumps and a monitoring and control system.

#### **SKID SHOES**

Each skid shoe consists of a triangular steel housing with an integrated vertical jack and a rocker bearing. Ground pressure is kept to a minimum by spreading the load over the length of the skid shoe. Options for further spreading of the load are available if required.

A simplified version called a skid beam can be used if the load does not need to be raised in the vertical direction



ТҮРЕ		SKID	PUSH-PULL UNIT			
	Capacity kN	Min. height mm	Stroke mm	Weight kg	Capacity kN	Stroke mm
VSS-90	880	645	150	585	200/120	600
VSS-150	1480	905	250	1000	200/120	600
VSS-300	2950	1355	400	3211	560/320	1250
VSS-500	4900	1485	600	4761	560/320	1250
VSS-750	7400	1542	600	8000	560/320	1250
VSS-1000	9900	1462	600	11600	560/320	1250

#### **PUSH-PULL UNITS**

Push-pull units are horizontal double-acting hydraulic jacks that supply the motive force needed to propel the complete system in either direction. They are connected to the tracks and the edges of the skid shoe.

#### SKID TRACKS

The skid shoes slide on the pads of a skid track. The skid tracks are U-shaped steel channels, which are connected together by a simple pin arrangement and contain integrated PTFE pads. A lubricant further reduces the friction.

#### **HYDRAULIC PUMPS**

VSS is operated using standard VSL electrohydraulic pumps. The size of the pump is chosen to suit the load being moved.

#### MONITORING AND CONTROL SYSTEM

The VSS enables precision-controlled movement to within millimetres, whether operated manually or by remote control. This precise coordination of all movements across every part of the system is achieved by using specially designed, computerbased multi-point monitoring systems, customised to the project's requirements.

#### SPECIAL FEATURES

Skidding tracks can be laid out on even ground without any fixings, including in situations with large-radius curves. Special skid tracks are available for use when moving loads along sharp curves.

A 2,500t tunnel boring machine was skidded 625 m overland. **TBM, Bienne - Switzerland (2010 and 2011)** 





Massive concrete caissons were skidded in their casting yard so that they could then be lowered into the sea by a VSL gantry. 
 Massive concrete caissons were skidded in their casting yard so that they could then be

 Each caisson weighed 3,400 t, measured 28 m by 28 m in plan view and was 10 m high.
MORE Tangiers Med 2 container port - Morocco (2011 - 2013)



TOGETHER N S

# **CREATING CONNECTIONS – BRIDGES**



Erection of arch segments for a striking 843 m-long bridge wouldn't have been possible without the expertise of the VSL Heavy Lifting team. The bridge's curved design symbolises sand dunes in the desert. Sheik Zayed Bridge, Abu Dhabi - UAE (2006-2010)







Space restrictions led to the development of a totally new method for launching the steel structures of two main viaducts. Cadagua Viaduct, Bilbao - Spain (2009 - 2010)

**CREATING S** 

10 vsl heavy lifting





A complete 740 m-long bridge was slid laterally following an earlier operation to lift the two middle spans from pontoons. Milton-Madison Bridge, linking Indiana and Kentucky - USA (2012 and 2014)





A 1,600 t centre span with a length of 55 m was lifted into place. Tseung Kwan O Bridge, Hong Kong - China (2012)



VSL was brought in to recover a 128 m-long steel bridge that had fallen into the river. The 550t bridge was then launched 36 m into position. **Omo Bridge - Ethiopia (2013)** 



Launching and lateral sliding operations were carried out for a 606 m-long replacement railway bridge. Rheinvorland Bridge, Worms - Germany (2010 - 2012)









# HIGH-LEVEL LIFTS – BUILDINGS







Building the world's highest 'sky bridge' involved lifting 750 t segments by 230 m. **Gate District Towers, Abu Dhabi - UAE (2011)** 

The roof of a massive aircraft hangar was lifted in two parts, weighing 970t and 770t. A380 Hangar, Toulouse - France (2013)

**CREATING** S

12 vsl heavy lifting



'he new stadium in Durban has a remarkable roof structure: a giant Y-shaped arch representing the South African flag. Its construction required the special installation of 'flying' - or self-climbing strand jacking units. **Moses Mabhida Stadium, Durban - South Africa (2008-2009)** 

# **AND STADIUMS**









The last pin: one of the largest cable-net roofs in the world was raised into place using 60 lifting points. **Maracanã Stadium, Rio de Janeiro -Brazil (2012-2013)** 



VSL carried out a complex operation to lift a 340t steel roof, transfer the load onto the permanent bearings and install a lighting ring. SSE Hydro Arena, Glasgow -Scotland (2012-2013)



With a lifting distance of 335 m VSL Heavy Lifting broke a new record when it raised three roof trusses on top of the ADNOC's new headquarters building. The trusses were then slid into their final positions. ADNOC Building, Abu Dhabi - UAE (2013)





Installation of the core element of a wind farm by involved lifting the 5,500 t hull and lowering the 3,500 t substructure. Global Tech I Platform, German North Sea - Germany (2012-2013)





 $Offshore\ installation\ of\ a\ self-elevating\ leg$ barge required VSL to lift a 2,300 t hull and lower four support legs, each weighing 145 t. Sanaga Leg Barge - Cameroon (2001-2012)

MORE



Cooling towers for a power plant were built in a dry dock before being transported by sea and then lowered into the water onto their foundations. Electrabel Power Plant, Wilhelmshaven - Germany (2013)

**C R E A T I N G** 



## **FLEXIBLE OPERATIONS – OFFSHORE**



More than 100 caissons were skidded and then towed into position to create new breakwaters. Tangiers Med 2 container port - Morocco (2011-2013)



Two 2,000t concrete caissons were lowered about 100 m onto the ground of a reservoir. Dam Reservoir, Emosson - Switzerland (2011 and 2012)



Risers and umbilical cables were lifted from a depth greater than 100 m onto a floating production storage and off-loading unit. The coilers for the operation were custom-made for the project. **USAN Deepwater Development Project - Nigeria (2011)** 

# **PRECISE INSTALLATION – INDUSTRY AND**



A 2,700t storage tank was lifted by 35 m. Abidjan Water Tower -Ivory Coast (2008)





VSL lifted a power plant's steel boiler components and some of the pipework. Power Plant Walsum Block 10 - Germany (2007-2008)

A machine-house gantry crane was replaced with a larger one. **Power Plant, Gösgen - Switzerland (2012)** 

**CREATING SO** 

# **ENERGY**

Three 180t dome-shaped roofs were raised about 70 m into their final positions using 16 lifting points. Al Khaleej Sugar Silo, Dubai - UAE (2011)







For the lifting and lowering operations at Europe's largest pumped storage plant, VSL Heavy Lifting developed a new tandem lifting/lowering system that allowed speeds of up to 40 m/h to be achieved. La Muela Hydroelectric Power Station - Spain (2009-2010)

Four Aalborg boilers were lifted at the energy recovery plant of one of the most energy-efficient ferrosilicon producers. Finnfjord energy recovery plant, Finnsnes - Norway (2011 and 2012)

### **CUSTOMISED SOLUTIONS – SPECIAL PROJECTS**





VSL carried out 1,400,000 test cycles over a six-month period to assess the performance of wind turbine foundations. Simulating the repeated wind and wave effects on the gravity foundation required the loading to be increased from 1,000 kN to 11,000 kN within just a few seconds. Wind turbine foundation testing, **Cuxhaven - Germany (2010-2011)** 





Record-breaking box-jacking was carried out to install two adjacent 65 m-long concrete tunnel modules underneath six live Queensland Rail lines. It is believed to be the world's largest single box-jack ever undertaken and required a design force of 360,000 kN on the largest box. Airport link, Brisbane - Australia (2011)



A 450 t pinnacle was lifted 89 m onto the top of the world's tallest building. Burj Khalifa, Dubai - UAE (2009)

VSL lowered into place 15 segments weighing between 250 t and 1,920 t for CERN's CMS detector, 97 m below ground. **CERN, Geneva - Switzerland (2004)** 

C R E A T I N G



## **RELIABILITY BASED ON PROVEN EXPERIENCE**



## 1970

**OLYMPIC STADIUM, MUNICH - GERMANY** First large-scale application of the VSL strand jacking technique, for the lifting and tensioning of the world-famous roof

## 1980

**SIA HANGAR, CHANGI AIRPORT - SINGAPORE** Lifting by 27 m of a stell roof structure weighing 3,600 t





# 985

NUCLEAR POWER PLANT, BEZNAU - SWITZERLAND Multiple operations carried out between 1985 and the present day, including the exchange of major components such as steam generators

### 1995

**PETRONAS TWIN TOWERS, KUALA LUMPUR - MALAYSIA** Lifting of a 325t 'sky bridge' to link the twin towers at a height of 170 m





# 2007

STONECUTTERS BRIDGE, HONG KONG - CHINA Lifting of bridge segments for one of the world's longest cable-stayed bridges

## IONS TOGETHER

vsl heavy lifting 19

### **VSL LOCATIONS**

Americas /

VSL Sistemas Especiales de

Construcción Argentina S. A.

Phone: +54 11 5272 87 52

VSL Brasil Construção e

Vorspann Systems Ltd

Phone: +1 416 477 1042

VSL Sistemas Especiales de

Phone: +56 2 2571 6700

Phone: +52 55 55 11 20 36

VSL Corporation Mexico S.A. de C.V.

UNITED STATES OF AMERICA

Construcción S.A.

Phone: +55 113 521 7153/4

Recuperação Ltda

ARGENTINA

**BUENOS AIRES** 

RRA7II

SÃO PAULO

CANADA

TORONTO

CHILE

SANTIAGO

MEXICO

MEXICO

PERU

LIMA

VSL PERU S.A.C

Phone: +51 1 713 9832

Structural Technologies \*

Phone: +1 410 850 7000

BALTIMORE. MD

#### HEADQUARTERS

VSL International Ltd. Saegestrasse 76 CH - 3098 Köniz Switzerland Phone: +41 58 456 3000 Email: info@vsl.com

### **Europe** /

**CZECH REPUBLIC** VSL Systémy /CZ/, s.r.o. PRAGUE Phone: +420 2 51 09 16 80

FRANCE VSL France S.A. (Bouygues TPRF) \* LABÈGE Phone: +33 05 33 65 96 59

POLAND VSL Polska Sp.o.o. WARSZAWA Phone : +48 22 849 22 09

PORTUGAL VSL Sistemas Portugal SA PACO DE ARCOS Phone: +351 21 445 83 10

SPAIN VSL Construction Systems SA BARCELONA Phone: +34 93 289 23 30

SWITZERLAND VSL (Switzerland) Ltd. SUBINGEN Phone: + 41 58 456 3030

SAINT LEGIER Phone: +41 58 456 3000

**UNITED KINGDOM** VSL System (UK) Ltd LUTON Phone: +44 148 040 44 01

VSL HEAVY LIFTING

Phone: +41 58 456 3030

www.vsl-heavy-lifting.com

hl.marketing@vsl.com

SWITZERLAND

SUBINGEN

(\*) Licencees



### Africa /

SOUTH AFRICA VSL Construction Solutions (Pty) Ltd \* JOHANNESBURG Phone: +27 10 492 1811

TUNISIA VSL Switzerland Tunisia Branch TIINIS Phone: +216 70 72 84 73

### Middle East /

SULTANATE OF OMAN VSL Muscat LLC MUSCAT Phone: +971 4 885 7225

**UNITED ARAB EMIRATES** VSL Middle East LLC DUBAI, UAE Phone: +971 4885 7225

DOHA, QATAR VSL Middle East (Qatar ) LLC ΠΠΗΔ Phone: +974 44 279 639

### Asia /

BRUNEI VSL Systems (B) Sdn. Bhd. BRUNEI DARUSSALAM Phone: +673 2 380 153 / 381 827

**CHINA PRC** VSL Engineering Corp., Ltd. (China) HEFEI Phone: +86 551 382 29 18

HONG KONG VSL Hong Kong Ltd. CHAI WAN Phone: +852 2590 22 88

INDIA VSL India Private Ltd. CHENNAI Phone: +91 44 4225 11 11

**INDONESIA** PT VSL Indonesia IAKARTA Phone: +62 21 570 07 86

JAPAN VSL Japan Corporation токуо Phone: +81 3 3346 8913

KOREA VSL Korea Co. Ltd. SEOUL Phone: +82 2 553 8200

MALAYSIA VSL Engineers (M) Sdn. Bhd. **KUALA LUMPUR** Phone: +60 3 7981 4742

**PHILIPPINES** VSL Philippines Inc. MANDALUYONG CITY Phone: +632 571 6203 SINGAPORE VSL Singapore Pte. Ltd. SINGAPORE Phone: +65 6559 12 22

TAIWAN VSL Taiwan Ltd. TAIPFI Phone: +886 2 2759 68 19

THAILAND VSL (Thailand) Co. Ltd. BANGKOK Phone: +66 2 679 76 15 - 19

VIETNAM VSL Vietnam Ltd. HANOI Phone: +84 4 3976 5088

HO CHI MINH CITY Phone: +84 8 810 6817

### Australia /

VSL Australia Ptv Ltd **NEW SOUTH WALES** Phone: +61 2 9484 5944

#### SPECIALIST SUBSIDIARIES

VSL Infrastructure **Protection Ltd** LONDON Phone: +44 207 803 3614 SINGAPORE Phone: +65 65 59 12 22 SYDNEY Phone: +61 2 94 84 5944

Intrafor Hong Kong Ltd. CHAI WAN, HONG KONG Phone: +852 2836 31 12 DUBAI, UAE Phone: +971 4 885 7225

FT Laboratories Ltd. PING CHE. HONG KONG Phone: +852 2758 48 61 **VSL Offshore Pte Ltd** SINGAPORE Phone: +65 6 559 13 05

Copyright 12/2015, VSL International Ltd.

Printed in Germany - patented The information set forth in this brochure including technical and engineering data is presented for general information only. While every effort has been made to insure its accuracy, this information should be accuracy in the set of not be used or relied upon for any specific application without independent professional examination and verification of its accuracy, suitability and applicability. Anyone using this material assumes any and all liability resulting from such use. VSL disclaims any and all express or implied warranties of merchantability fitness for any general or particular purpose in regard to the information or products contained or referred to herein. Nothing herein contained shall be construed as granting a license, express or implied under any patents

WWW.VSL.COM